

Digital Signage

Lighter, thinner and more portable



Sturdy
Structure



Ultra-narrow
Bezel



1080P / 4K
Ultra HD



Free
CMS



Dual
Orientation



Android 14.0
(Custom Ver.)

Features

Sleek & Slim Design



3 Brightness Levels Optional




Ultra-narrow Equal Bezel



High Color Gamut



Free CMS




Application



Tea shop



Mall



Exhibition



Hospital

Model	DS30-032B66N	DS30-043B66N	DS30-049B66N	DS30-055B66N
LCD Panel Parameters				
Diagonal Size	32"	43"	49"	55"
Resolution	1920×1080	1920×1080	1920×1080	3840×2160
Brightness (Typ.)	350cd/m ² (500/700 optional)	350cd/m ² (500/700 optional)	350cd/m ² (500/700 optional)	350cd/m ² (500/700 optional)
Contrast Ratio (Typ.)	4000:1	4000:1	4000:1	4000:1
Viewing Angle (V/H)	178°/178°	178°/178°	178°/178°	178°/178°
Visible Area (mm)	697.7×392.2	940.9×529.3	1073.8×604.0	1209.6×680.4
Color Gamut	DCI-P3 95%	DCI-P3 95%	DCI-P3 95%	DCI-P3 95%
Aspect Ratio	16:9	16:9	16:9	16:9
System Configuration				
System Version	Android 14.0	Android 14.0	Android 14.0	Android 14.0
CPU	Quad-core Cortex-A55	Quad-core Cortex-A55	Quad-core Cortex-A55	Quad-core Cortex-A55
GPU	Mali-G52	Mali-G52	Mali-G52	Mali-G52
Main Frequency	1.8GHz	1.8GHz	1.8GHz	1.8GHz
RAM	2G(4G optional)	2G(4G optional)	2G(4G optional)	2G(4G optional)
Storage (Flash)	32G(8G/64G optional)	32G(8G/64G optional)	32G(8G/64G optional)	32G(8G/64G optional)
Network	Ethernet,Wi-Fi, Wireless peripheral expansion	Ethernet,Wi-Fi, Wireless peripheral expansion	Ethernet,Wi-Fi, Wireless peripheral expansion	Ethernet,Wi-Fi, Wireless peripheral expansion
Speaker	2×8Ω/5W(built-in)	2×8Ω/5W(built-in)	2×8Ω/5W(built-in)	2×8Ω/5W(built-in)
Interface	USB 2.0×2, RJ45×1, TF Slot×1, Earphone Jack×1, HDMI OUT×1	USB 2.0×2, RJ45×1, TF Slot×1, Earphone Jack×1, HDMI OUT×1	USB 2.0×2, RJ45×1, TF Slot×1, Earphone Jack×1, HDMI OUT×1	USB 2.0×2, RJ45×1, TF Slot×1, Earphone Jack×1
Power Characteristics				
Power Input	AC/100V~240V	AC/100V~240V	AC/100V~240V	AC/100V~240V
Standby Power Consumption	≤0.5W	≤0.5W	≤0.5W	≤0.5W
Typical Power Consumption	35W	50W	85W	90W
Dimensions				
Unit Dimensions (mm)	733.7×431.2×42.2 (without Mounting Bracket) 733.7×431.2×60.2 (with Mounting Bracket)	975.5×564.6×42.2 (without Mounting Bracket) 975.5×564.6×69.2 (with Mounting Bracket)	1107.8×637.5×42.2 (without Mounting Bracket) 1107.8×637.5×69.2 (with Mounting Bracket)	1243.0×713.8×42.2 (without Mounting Bracket) 1243.0×713.8×69.2 (with Mounting Bracket)
Package Dimensions (mm)	800.0×545.0×145.0	1045.0×680.0×145.0	1180.0×760.0×145.0	1320.0×830.0×145.0
Net Weight	7kg	10.4kg	12.9kg	15.3kg
Gross Weight	10kg	14.5kg	18kg	21kg
Environment				
Operating Temperature	0°C~50°C	0°C~50°C	0°C~50°C	0°C~50°C
Operating Humidity	10%RH~90%RH	10%RH~90%RH	10%RH~90%RH	10%RH~90%RH
Standard Accessories				
Documents	User Manual×1	User Manual×1	User Manual×1	User Manual×1
Accessories Enclosed	Mounting Bracket ×1, Screw Pack ×1, Wifi Antenna Pole×1, Remote Control×1	Mounting Bracket ×1, Screw Pack ×1, Wifi Antenna Pole×1, Remote Control×1	Mounting Bracket ×1, Screw Pack ×1, Wifi Antenna Pole×1, Remote Control×1	Mounting Bracket ×1, Screw Pack ×1, Wifi Antenna Pole×1, Remote Control×1
Cables	AC Power Cord 1.5m×1	AC Power Cord 1.5m×1	AC Power Cord 1.5m×1	AC Power Cord 1.5m×1


Certificate









Introduction



Installation



Official Website