

Digital Signage

Zero gap against wall

DS60 Series



1080P / 4K
Ultra HD



Free
CMS



Dual
Orientation



UL94 V-0
Fireproof Shell



25% Haze
Matte Screen
(optional)




Android 14.0
(Custom Ver.)

Features

High Color Gamut



25% Haze Matte Screen (optional)




Ultra-slim

28.5mm



* Some sizes excluded.

Zero-wall design



Built-in Free CMS




Application



Super Mall



Apparel



Catering



Transportation

Model	DS60-043B50N	DS60-050B82N	DS60-055B82N	DS60-065B82N
LCD Panel Parameters				
Diagonal Size	43"	50"	55"	65"
Resolution	1920×1080	3840×2160	3840×2160	3840×2160
Brightness (Typ.)	500cd/m²(350/700 optional)	500cd/m²(350/700 optional)	500cd/m²(350/700 optional)	500cd/m²(350/700 optional)
Contrast Ratio (Typ.)	4000:1	4000:1	4000:1	4000:1
Viewing Angle (V/H)	178°/178°	178°/178°	178°/178°	178°/178°
Visible Area (mm)	946.4×536.1	1100.2×620.9	1215.0×687.1	1433.6×810.2
Color Gamut	DCI-P3 95%	DCI-P3 95%	DCI-P3 95%	DCI-P3 95%
Aspect Ratio	16:9	16:9	16:9	16:9
System Configuration				
System Version	Android 14.0	Android 14.0	Android 14.0	Android 14.0
CPU	Quad-core A53	Quad-core A55	Quad-core A55	Quad-core A55
GPU	Mali-450	Mali-G52	Mali-G52	Mali-G52
Main Frequency	1.5GHz	1.8GHz	1.8GHz	1.8GHz
RAM	1G	2G	2G	2G
Storage (Flash)	8G	32G	32G	32G
LAN	100M Ethernet	100M Ethernet	100M Ethernet	100M Ethernet
WIFI	IEEE 802.11a/b/g/n/ac/ax, Bluetooth 5.4	IEEE 802.11a/b/g/n/ac/ax, Bluetooth 5.4	IEEE 802.11a/b/g/n/ac/ax, Bluetooth 5.4	IEEE 802.11a/b/g/n/ac/ax, Bluetooth 5.4
Speaker	2×8Ω/5W(built-in)	2×8Ω/5W(built-in)	2×8Ω/5W(built-in)	2×8Ω/5W(built-in)
Interface	DC×1, RJ45×1, HDMI IN×1, USB 2.0×2, TF Slot×1, 3.5mm Jack×1	DC×1, RJ45×1, HDMI IN×3, USB 2.0×1, USB 3.0×1, TF Slot×1, 3.5mm Jack×1	DC×1, RJ45×1, HDMI IN×3, USB 2.0×1, USB 3.0×1, TF Slot×1, 3.5mm Jack×1	DC×1, RJ45×1, HDMI IN×3, USB 2.0×1, USB 3.0×1, TF Slot×1, 3.5mm Jack×1
Power Characteristics				
Power Input	AC/100V~240V	AC/100V~240V	AC/100V~240V	AC/100V~240V
Standby Power Consumption	≤0.5W	≤0.5W	≤0.5W	≤0.5W
Typical Power Consumption	100W	120W	130W	150W
Dimensions				
Unit Dimensions (mm)	969.4×559.1×28.5	1123.2×643.9×28.5	1238.0×710.1×28.5	1456.6×833.2×30.0
Package Dimensions (mm)	1063.6×676.8×146.0	1218.2×763.9×146.0	1332.0×843.0×146.0	1551.6×953.0×146.0
Net Weight	9.8kg	13.4kg	16.0kg	27.8kg
Gross Weight	12.7kg	16.3kg	18.8kg	30.9kg
Environment				
Operating Temperature	0°C~50°C	0°C~50°C	0°C~50°C	0°C~50°C
Operating Humidity	10%RH~90%RH	10%RH~90%RH	10%RH~90%RH	10%RH~90%RH
Standard Accessories				
Documents	User Manual×1	User Manual×1	User Manual×1	User Manual×1
Accessories Enclosed	Antenna×1, Remote Control×1, Wall Mounting Plates×2, Screw Kit×1	Antenna×1, Remote Control×1, Wall Mounting Plates×2, Screw Kit×1	Antenna×1, Remote Control×1, Wall Mounting Plates×2, Screw Kit×1	Antenna×1, Remote Control×1, Wall Mounting Plates×2, Screw Kit×1
Cables	AC Power Cord 1.5m×1	AC Power Cord 1.5m×1	AC Power Cord 1.5m×1	AC Power Cord 1.5m×1

Certificate

FC

CE

CB

Introduction

Installation

Official Website